

NECKREST FOR A CHAIR

BACKGROUND OF THE INVENTION

Field of the Invention

5 The present invention generally relates to sitting furniture and more particularly, to a neckrest, for a chair having backrest, configured to be attached to a backrest shield in a height-adjustable manner, the neckrest including a circular cross-section retaining rod, configured to be connected to the backrest shield in an articulating or movable manner so as to be tiltable by up to approximately 30° in a vertical plane vertically with respect to a surface of the backrest, and a circular cross-section guide sleeve, mounted on the retaining rod so as to be slidingly shiftable by up to approximately 200 mm on the retaining rod.

Discussion of Background

15 It is known that the user of a chair, in particular an office chair or other type of work-related chair, often has the need for relaxation, which the user may accomplish by leaning back. According to the latest medical findings, optimal relaxation is achieved with an angle of opening between upper and lower body of about 25°. For this purpose, many chairs are equipped with a tiltable backrest.

20 One type of chair having a tiltable backrest is a so-called "high-back" chair. These "high-back" chairs often have the problem that the upper part of the backrest also supports the head or the neck, and this support of the head or the neck cannot be adjusted to the individual requirements of the user. Further, in the case of chairs with a low backrest, the headrest cannot be brought easily into the area of the head of the user.

SUMMARY OF THE INVENTION

It is therefore an object of the present invention to provide a neckrest for a chair having a backrest which is designed in such a way that the neckrest can be attached inconspicuously and aesthetically on the back shield of a chair with backrest, but that nevertheless the headrest covers the entire angular range, within which the user wants to rest his head against the pad. Furthermore, the neckrest of the present invention should be able to be manufactured in production with little effort and easily mountable on the chair having the backrest.

The above-stated objective is accomplished with by the neckrest of the present invention, wherein the neckrest is for a chair having a backrest, the neckrest configured to be attached to a backrest shield in a height-adjustable manner. The neckrest including a circular cross-section retaining rod, configured to be connected to the backrest shield in an articulating manner so as to be tiltable by up to 30° in a vertical plane vertically with respect to a surface of the backrest, and a circular cross-section guide sleeve, mounted on the retaining rod so as to be slidingly shiftable by up to 200 mm on the retaining rod.

In other words, the neckrest of the present invention includes connecting the headrest of the chair on a guide sleeve that slides on a retaining rod, fastening the retaining rod on the back shield through a simple joint in a tiltable manner, and designing the retaining rod and guide sleeve so as to have circular cross-sections. On the one hand, this allows the user to adjust the desired inclination of the neckrest in a simple manner. On the other hand, the height of the neckrest is also adjustable. It is very important that the retaining rod and the guide sleeve are designed so as to have circular cross-sections because, unlike a straight retaining rod, the circular cross-section retaining rod allows for an adjustment of the optimal distance of the headrest from the head of the user.

BRIEF DESCRIPTION OF THE DRAWING FIGURES

The present invention is explained in more detail in the following based on one example shown in the drawing figures, wherein:

Fig. 1 is a side elevational view of a chair with a backrest having the attached neckrest
5 of the present invention;

Fig. 2 is a cross-sectional view through the neckrest of the present invention with a headrest that is firmly attached to the guide sleeve; and

Fig. 3 is a cross-sectional view through the upper part of the neckrest of the present invention with a headrest that is attached to the guide sleeve in an articulating manner.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1 depicts an office chair 11, which contains the familiar lower base, a seat, and a backrest. The neckrest of the present invention includes a retaining rod 3, a guide sleeve 4, and a headrest 5 and is attached on the back of the backrest. The backrest and the seat can be tilted in the familiar fashion, wherein in the example shown in the figure, a synchronous
5 mechanism is provided.

Fig. 2 shows the neckrest of the present invention in detail in a cross-sectional view. More particularly, the base plate 2 of the backrest pad is snapped on to the backrest shield 1. A housing 9 is provided over a portion of the back of the backrest shield 1. The housing 9 includes a recess 9a. The housing 9 is attached to the backrest shield 1 via the fastening plate
20 10. Fastening occurs using four screws (not shown), which penetrate the fastening plate 10 and the backrest shield 1 and which are screwed into screw domes (not shown) of the housing 9. In the housing 9, the retaining rod 3 is seated via a molding 3a. The molding 3a rests against the friction dampening device 7 when under pressure. The friction dampening device

7 preferably includes a polyurethane rubber or PUR material. The friction dampening device 7 is preferably held in the dampening sleeve 8. The dampening sleeve 8 is shaped from the fastening plate 10 in a combined cutting and bending process and the dampening sleeve 8 is preferably connected with the fastening plate 10.

5 The retaining rod 3 penetrates the housing 9 in the recess 9a of the housing 9. The recess 9a is designed in such a way that the retaining rod 3 can perform an inclination by up to approximately 30°, and more preferably by approximately 23°. In doing so, the retaining rod 3 is held in each position by the friction force of the friction dampening device 7.

10 The retaining rod 3 is designed so as to be circular in cross-section. The guide sleeve 4 is seated on the retaining rod 3 in a sliding manner, the guide sleeve 4 also being designed so as to be circular in cross-section with the same radius as the radius of the circular cross-section retaining rod 3. The headrest 5 is firmly attached on the end of the guide sleeve 4. The guide sleeve 4, and with it the headrest 5, can be height adjustable in a sliding manner on the retaining rod 2 by up to approximately 200 mm, but more preferably by approximately 150 mm. On one hand, the roller bearing elements 12, which consist of a polyurethane rubber or PUR material, cause the guide sleeve 4 to be moved easily. On the other hand, the roller bearing elements 12 remain fixed in the position adjusted by the user.

20 In order to ensure that the guide sleeve 4 cannot be pulled off the retaining rod 3, a stop screw 6 is provided in the guide sleeve 4, with the stop screw 6 limiting the path of the guide sleeve 4 due to the stop on the lug 6a of the retaining rod 3.

Sup Fig. 3 shows the neckrest of the present invention as shown in Fig. 2, However, the neckrest shown in Fig. 3 has the head-rest 5 connected to the guide sleeve 4 via a joint including a rolling element 15 and a fastening device 16.

More particularly, Fig. 3 illustrates the headrest shield 14 having a plate 13 and the

head-rest 5 snapped thereon. The guide sleeve 4 contains a rolling element 15, which is seated in a fastening device 16 shaped from the head-rest shield 14. The rolling element 15 can be designed as a ball or circular cylinder. As can be seen, with this articulating connection the user can adjust the head-rest 5 in a cardanic manner (in the case of the ball) or in a sagital manner (in the case of the circular cylinder) in accordance with his needs to any suitable position.

The present invention makes it possible to attach a neckrest, which is tiltable and height adjustable, to the backrest of a chair having a backrest in a simple, yet aesthetically pleasing manner, and to enable the user to adjust the neckrest to any ergonomically desirable position. Further, the production effort for the neckrest of the present invention is modest and assembly is easy.

~~List of Reference Numerals~~

- | | |
|----|---------------------------|
| 1 | Backrest Shield |
| 2 | Pad Plate |
| 3 | Retaining Rod |
| 3a | Molding |
| 4 | Guide Sleeve |
| 5 | Headrest |
| 6 | Stop Screw |
| 6a | Stop Lug |
| 7 | Friction Dampening Device |
| 8 | Dampening Sleeve |
| 9 | Housing |

- 9a Recess
- 10 Fastening Plate
- 11 Chair
- 12 Roller Bearing Element
- 13 Headrest Plate
- 14 Headrest Shield
- 15 Rolling Element
- 16 Fastening Device

5

20150417 013103

W.S.
A4